

CLAIMS

1. A method of transmitting information in a radio communication system comprising at least one transmitter and at least one receiver, the method comprising the steps of:

- Transmitting first information in a first channel from the at least one transmitter to the at least one receiver, using in the transmitting a modulation and/or coding scheme and adapting the modulation and/or coding scheme to give a secure communication of the first information, and
- Transmitting second information in a second channel from the at least one transmitter to the at least one receiver and setting the power used for transmitting in the second channel to give a secure communication of the second information, **characterized** in that in the step of transmitting, the first information, the choice of the modulation and/or coding scheme is controlled by the level of the power at each instant set for transmitting in the second channel.

2. Method according to claim 1, **characterized** in that the second channel is transmitted from the same transmitter as the first channel.

3. Method according to claim 1, **characterized** in that the second channel is transmitted from one of a plurality of transmitters, comprising the transmitter that transmits the first channel.

4. Method according to any of claim 1-3, **characterized** in that the first physical channel is shared between several users and in that each user has a unique second channel wherein the modulation and coding scheme used by the first channel is determined by the instantaneous transmitted power of the

second channel, the user of the second channel being currently served by the first channel.

5. Method according to any of claim 1-4, **characterized** in that
5 the transmitter is a base station and the receiver is a mobile station.
6. Method according to any of claim 1-5, **characterized** in
10 that the first channel is a shared downlink channel and the second channel is a dedicated physical channel.
7. Method according to claim 6, **characterized** in that the
15 modulation and/or coding scheme used on the downlink shared channel when transmitting to a specific receiver is controlled by the power control commands transmitted by the receiver in the reverse link.
8. A method according to claim 7, **characterized** in that the
20 power control commands are transmitted in combination with other information.
9. A method according to any of claim 6-8, **characterized** in
25 that the power of the dedicated physical channel is mapped into a suitable modulation and coding scheme for the downlink shared channel.
10. A method according to claim 9, **characterized** in that a
30 varying modulation and coding scheme is used on the downlink shared channel.
11. A method according to claim 9, **characterized** in that the
mapping is static.
12. A method according to claim 9, **characterized** in that the
35 mapping is dynamic.

13. A method according to claim 11, **characterized** in that a predefined table is use for mapping the power level to the modulation and coding scheme.

5 14. A method according to claim 12, **characterized** in that the mapping is changed as a function of some retransmission requests for data blocks being retransmitted over the shared channel.

10 15. A method according to claim 12, wherein at least two base stations are transmitting at the same time to the same mobile station, **characterized** in that that the power of the DPCH is multiplied with a constant k , $k \geq 1$, said constant being used for determining the modulation and coding scheme
15 of the DSCH, both channels DPCH and DSCH transmitting from the same base station.

20 16. A method of modifying the transmission parameters in a radio communication system comprising at least one transmitter, at least one receiver, a first channel for transmitting first information from the at least one transmitter to the at least one receiver, and a second channel for transmitting second information from the at least one transmitter to the at least one receiver, the
25 method comprising the steps of

- Setting the power used for transmitting in the second channel; and
- Adapting a modulation and/or coding scheme used in transmitting in the first channel, **characterized** in that in
30 the step of adapting, the choice of the modulation and/or coding scheme is controlled by the level of the power at each instant set for transmitting in the second channel.

35 17. Method according to claim 16, wherein at least two transmitters are transmitting at the same time,

09873309 060501
T0590" 60527860

-